



MAC PLANTMASTER S.S.

The MAC Plantmaster is now available in full stainless steel to meet the growing demand for quality and durability



KEY SPECIFICATION

Hot Water Static

12ltr, 15ltr or 21ltr/min
Water Flow

100bar or 200bar Pressure

240v or 415v Power Supply

High Pressure Chemical

Full Frost Protection



MAC PLANTMASTER S.S.



STANDARD FEATURES

- High quality, full stainless steel cabinet
- Full frost protection and cabinet lagging
- Lockable stainless steel front door
- Efficient M2 boiler system
- Flame failure and leak detection
- 16lt fuel tank with low level sensor as standard
- Professional Interpump with ceramic pistons
- Industrial 1450rpm 4 pole electric Nicolini motor
- Automatic stop/start system
- High pressure chemical system
- Bypass and safety valve
- Burner control with flow switch and thermostat
- 24v low tension safety

CHOOSE FROM A WHOLE HOST OF BESPOKE OPTIONS AND ACCESSORIES:

- **Internal and external hose reels**
- **Upgraded fuel and water tanks**
- **Key fob and remote control systems**
- **Timed and non-timed chemical systems**



FLAME FAILURE AND
LEAK DETECTION SYSTEM



30 SECOND
AUTO STOP/START

	PLANTMASTER/SS1	PLANTMASTER/SS2	PLANTMASTER/SS3	PLANTMASTER/SS4
Water Flow	12lt per minute	15lt per minute	15lt per minute	21lt per minute
Pressure	100bar, 1500psi	150bar, 2200psi	200bar, 3000psi	200bar, 3000psi
Motor Specification	3hp, 1450rpm	5.5hp, 1450rpm	7.5hp, 1450rpm	10hp, 1450rpm
Chemical	High Pressure	High Pressure	High Pressure	High Pressure
Shutdown System	Auto Stop/Start	Auto Stop/Start	Auto Stop/Start	Auto Stop/Start
Temperature	0-100°C	0-100°C	0-100°C	0-100°C
Power	240v	415v	415v	415v
Weight	230kg	240kg	250kg	270kg
Dimensions (h x w x d)	160 x 82 x 56cm	160 x 82 x 56cm	160 x 82 x 56cm	160 x 82 x 56cm