


MAC PERMAHOT LASER

PERMANENTLY HOT WATER

- Electrically heated mobile
- 90°C constant temperature
- Low water consumption
- 415v - 32 Amp supply
- Strong stainless steel construction
- Patented hot water design

PERMAHOT



KEY SPECIFICATION

Electrically Heated Mobile

6ltr/min Water Flow

150bar Pressure

90°C Constant Temperature

415v, 32amp Power Supply

MAC PERMAHOT LASER

PERMAHOT

STANDARD FEATURES

- 90°C Constant Temperature
- Patented 3 x 4kw Solid Element system
- Full stainless steel chassis and cover
- Front and rear chassis protection bars
- 4 large robust wheels for tough terrain
- Professional Interpump with ceramic pistons
- Industrial 1450rpm low rewinding electric motor
- Instant stop system
- Stainless steel water tank with low water cut off switch
- Water softener system
- Bypass valve
- Pressure gauge
- Heater on/off switch
- Mains on lamp & heating element lamp
- Heater controlled by thermostat
- 24v low tension safety controls
- Current thermal overload protection
- Stainless steel manual hose reel & stainless steel basket for accessories - Permahot Laser
- Including 15mt hose, 900mm quick release lance and heavy duty trigger



VIEW THE PERMAHOT PRODUCT VIDEO AT
WWW.PERMAHOT.CO.UK

The Permahot range utilises our patented 3 x 4kw solid element heating system.

It is now possible to produce 90°C constant heat, on a standard 415v, 32amp power supply.

Perfect for food environments and all conditions where diesel, fumes and large water consumption are major problems.

MAC64 - MOBILE

| | |
|------------------------|-----------------|
| Water Flow | 6lt per minute |
| Pressure | 150bar, 2200psi |
| Motor Specification | 5.5hp, 1450rpm |
| Shutdown System | Instant Stop |
| Temperature | 0-90°C Constant |
| Power | 415v, 32amps |
| Weight | 100kg |
| Dimensions (h x w x d) | 97 x 60 x 106cm |