

# MAC FIX HT

## Designed to Utilise On-Site Hot Water

- Up to 85°C inlet temperature
- High temperature Interpump
- Overtemp sensor as standard



### KEY SPECIFICATION

Cold Water Module

11ltr or 18ltr/min Water Flow

100bar or 160bar Pressure

240v or 415v Power Supply



# MAC FIX HT



## STANDARD FEATURES

- Stainless steel wall mounted cabinet
- Stainless steel wall mounting bracket
- High temperature Interpump to accept up to 85°C water
- Industrial 1450rpm low revving electric motor
- Automatic stop/start system
- Bypass valve
- Pressure gauge
- Mains on lamp
- 24v low tension safety controls
- Including 10mt hose, lance and heavy duty trigger and stainless steel wall mounting bracket

## OPTIONAL ACCESSORIES

- Plastic or stainless steel water tank
- Frost protection
- Stainless steel floor stand
- Remote control system
- Low pressure chemical injector with twin lance



	MAC13HT	MAC14HT	MAC15HT
<b>Water Flow</b>	11lt per minute	13lt per minute	18lt per minute
<b>Pressure</b>	100bar, 1500psi	170bar, 2465psi	160bar, 2320psi
<b>Motor Specification</b>	3hp, 1450rpm	5.5hp, 1450rpm	7.5hp, 1450rpm
<b>Chemical</b>	Low Pressure	Low Pressure	Low Pressure
<b>Shutdown System</b>	Auto Stop/Start	Auto Stop/Start	Auto Stop/Start
<b>Power</b>	240v	415v	415v
<b>Weight</b>	60kg	70kg	80kg
<b>Dimensions (h x w x d)</b>	40 x 76 x 47cm	40 x 76 x 47cm	40 x 76 x 47cm